

# BESTOLIFE 2000® AG



5 Gallon Plastic Pail

## PRODUCT CHARACTERISTICS

|  |   |
|--|---|
| <b>Color:</b>                          | Dark Copper                                   |
| <b>Penetration:</b><br>(ASTM D217)     | 320 - 340                                     |
| <b>NLGI Grade:</b>                     | 1   |
| <b>Weight/Gallon:</b>                  | 10.7 pounds/gallon                            |
| <b>Thickener:</b>                      | Calcium 12 Hydroxy                            |
| <b>Fluid Type:</b>                     | Petroleum                                     |
| <b>Dropping Point:</b><br>(ASTM D2265) | ≥300°F (≥149°C)                               |
| <b>Flash Point:</b>                    | ≥325°F (≥162°C)                               |
| <b>Brushable To:</b>                   | -40°F (-40°C)                                 |
| <b>Service Rating:</b>                 | 400°F (204°C)                                 |
| <b>Friction Factor:</b>                | .9*   |
| <b>Contains:</b>                       | Inert nonmetallic solids and <4% copper flake |

\*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary Shouldered Connections"

Note: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

## DESCRIPTION

BESTOLIFE 2000® AG (Arctic Grade) is a lead-free, zinc-free thread compound for casing, tubing, and line pipe that applies smoothly at cold temperatures. An excellent running compound, 2000® AG (Arctic Grade) also provides superior storage protection.

## APPLICATIONS

Premium arctic grade thread compound for casing, tubing, and line pipe.

## TECHNICAL DATA

Extensive controlled testing, including full-scale make and break and sustained gas pressure tests on the same solids formulations found in the "2000®" series of products, indicates that 2000® AG (Arctic Grade) will meet or exceed the listed performance objectives in API RP 5A3. The major solid components of 2000® AG (Arctic Grade) are a proprietary blend of nonmetallic materials that are inert to chemical attack, such as occurs in sour gas environments and with CO2 injection.

## PACKAGING

| PRODUCT NUMBER | CONTAINER SIZE | CONTAINER WEIGHT  |
|----------------|----------------|-------------------|
| 615014         | 2 gallon       | 18 pounds metal   |
| 615015         | 2 gallon       | 18 pounds plastic |
| 615032         | 3 1/2 gallon   | 30 pounds metal   |
| 615047         | 5 gallon       | 45 pounds plastic |

Note: All package sizes are not listed. Call your sales representative for a complete listing.



**BESTOLIFE**  
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

**BESTOLIFE.COM**