

BESTOLIFE No. 270®



3 1/2 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color:	Black
Penetration: (ASTM D217)	290-310
NLGI Grade:	1.5
Weight/Gallon:	19.6 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	≥392°F (≥200°C)
Brushable To:	10°F (-12°C)
Friction Factor:	1.0*
Contains:	Over 60% metallic lead and other nonmetallic additives

*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

Note: All package sizes are not listed. Call your sales representative for a complete listing.

DESCRIPTION

The original BESTOLIFE No. 270® is a patented formulation for rotary-shouldered connections. It combats galling, seizing, and downhole makeup.

APPLICATIONS

Premium drill collar compound provides maximum protection. Recommended for drill collars, tool joints, casing, tubing, pipe joints, studs, bolts, nuts and screws, gaskets, high temperature flange connections, pumps, exhaust lines and pipeline connections.

TECHNICAL DATA

BESTOLIFE No. 270® is a superior thread compound that contains over 60% pure metallic lead and special non-metallic additives. This premium compound provides maximum protection of drill collars, drill pipe and all threaded connections, except oxygen lines. BESTOLIFE No. 270® provides a stable seal under all conditions and is not attacked by H₂S or drilling fluids. Meets the requirements of API RP SPEC 7: "Specification for Rotary Drill Stem Elements".

NOTES

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
600114	1 gallon	14 pounds plastic
600150	3 1/2 gallon	50 pounds metal



BESTOLIFE
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

BESTOLIFE.COM