

COLLAR PIPE PLUS



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color:	Black
Penetration: (ASTM D217)	275-295
NLGI Grade:	1.5
Weight/Gallon:	10.9 pounds/gallon
Thickener:	Calcium 12 Hydroxy
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥300°F (≥149°C)
Flash Point:	≥325°F (≥162°C)
Brushable To:	-32°F (-36°C)
Service Rating:	400°F (204°C)
Friction Factor:	1.0*
Shelf Life: (Unopened container)	4 years
Contains: Copper flake, synthetic and amorphous graphite and other nonmetallic additives	

*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

DESCRIPTION

Collar Pipe Plus thread compound contains >50% solids to protect and seal connections.

APPLICATIONS

Thread compound suited specifically for the Canadian drilling environment.

TECHNICAL DATA

Collar Pipe Plus contains a high percentage of graphite and other inert solids that provide thread protection and sealing over a wide range of conditions and temperatures. The excellent sealing properties make it an ideal thread sealant and lubricant for any threaded connection where contact bearing stresses are not extreme.

Collar Pipe Plus will adhere to wet connections including oil, water and polymer based drilling fluids, will apply readily over a wide range of temperatures and will not harden with exposure or age.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
652457	5 gallon plastic	35 lb/15.88 kg

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

CPP
DISTRIBUTION

sales@cppdist.com | cppdist.com

TF 1.800.871.4160 | CAN 780.438.0483 | USA 832.557.5663

