

## **ChemStar Mechanical Packing, Inc.**

**Address:** 3010 Reynolds Rd  
Lakeland, FL 33803 USA  
**Office:** (863) 425-5581 / (800) 397-5581  
**Fax:** (863) 425-5762  
**Email:** sales@chemstarpacking.com  
**Website:** www.chemstarpacking.com



### **STYLE 165**



- **Temperature:** To 550°F / 285°C
- **pH Range:** 0-14
- **Speed:** 4300 FPM
- **Pressure:** 300 PSI / 20 Bar
- **Construction:** Interlock Braid

**Description:** 100% GFO graphite filled PTFE fiber with excellent thermal conductivity and chemical resistance. 165 is flexible and pliable and will not harden, swell or become brittle. Packing is stamped with 100% GFO for your reassurance.  
*(ChemStar is a registered seal of assurance braider with W. L. Gore)*

**Equipment:** Valves, agitators, mixers, driers, refiners, rotating & reciprocating equipment, expansion joints

**Applications:** Corrosives, chemicals, solvents, water, steam, gases, air, ammonia, oils, liquor, paper stock, condensate. Marine shaft packing that is ABS approved and used by the U.S. Navy.

**Industries:** Agriculture, Chemical & Pharmaceutical, General industry, Marine, Municipal/Wastewater, Oil & Gas, Power generation, Pulp & Paper and Steel & Metals